

# H2ONDA Slim

ABOVE SINK WATERCOOLER || ELECTRIC SUPPLY

From the combination of elegance and quality comes **H2Onda Slim**: a small and modern dispenser that fits perfectly in every house.

*As standard, the dispenser is equipped with anti- flooding and LED bactericidal system.*

## AVAILABLE COMBINATIONS COLOURS

BACK/ FRONT:

- ★ WHITE/WHITE
- ★ BLACK/BLACK
- ★ STEEL/WHITE
- ★ STEEL/BLACK
- ★ STEEL/GREY



Dispenser	Production of cooled water	Cooling	Weight	Sizes (LXPXH) *
H2Onda Slim Plus 3 supplies	15 l/h	storage tank	16 Kg	20x35x44 cm
H2Onda Slim Natural 2 supplies	15 l/h	storage tank	13 Kg	20x35x44 cm

\*drip tray included

*The production of still and sparkling cold water, below 10°C, is closely linked to the room temperature but mainly to the inlet water temperature.*

# H2ONDA Slim

ABOVE SINK WATERCOOLER || ELECTRIC SUPPLY

## TECHNICAL CHARACTERISTICS:

**Material of the bodywork:** Painted sheet metal

**Water pressure:** 1-3,5° bar

**Max inlet temperature:** 35°

**Water feeding (min-max):** 10-25°C

**Feeding:** 220v - 50 Hz

On/off button (only in natural version)

## DISPENSER || H2Onda Slim

**Compressor:** 1/ 20" Hp

**Storage tank capacity:**

- 1,6 Natural version
- 2,5 l Plus version

**Carbonator capacity:** 100 l/h

**Carbonator pump:** Booster 100 l/h

**Recirculating pump:** NOT PROVIDED

**Power consumption:** 220 W

**Voltage:** 230 V- 50 Hz



**CERTIFIED PRODUCT**  
MATERIALS IN CONTACT WITH WATER



USABLE WITH A FILTER WATER CARE FILTERS.



**USABLE ONLY WITH DRINKING WATER.**



EQUIPMENT COMPLIES WITH:  
D.M. 25/2012 - D.M. 174/2004

NOTE: This equipment requires regular maintenance periodically to ensure the requirements of potability of the drinking water treated and maintenance improvements as declared by the producer. Do not use with microbiologically dangerous water. After long periods of inactivity (3-4 weeks) to keep it carefully sanitizing or provide for the replacement of the filter.