



H2ONDA HOT

COUNTER TOP DISPENSER || ELECTRIC SUPPLY

PRESS THE TWO BUTTONS AT THE SAME TIME TO DISPENSE HOT WATER

It's born from the reliability of a model with consolidated performance

H2Onda Hot, the design solution for all those who love enjoy a hot drink.

Ideal for the infusion of tea and herbal teas.

Performance and quality from the first delivery.

The equipment is standard equipped with an anti-flooding system and a UV LED bactericide system.

AVAILABLE COLOUR

BODYWORK/ FRONT:

★ WHITE/WHITE



STAND BY :

- Scheduled after 30 minutes;
- By pressing a hot water button for 3 seconds.

Dispenser	Productivity	Cooling	Weight	Dimensions (LXPXH) * OVERCOUNTER
H2Onda Plus 4 distributions	15 l/h	accumulation	23 Kg	28x43x41
H2Onda Natural 3 distributions	15 l/h	accumulation	17 Kg	28x43x41

* including drip tray

The production of still and / or sparkling cold water, below 10 ° C, is closely linked to the ambient temperature but mainly to the temperature of the incoming water.



H2ONDA HOT

COUNTER TOP DISPENSER || ELECTRIC SUPPLY

PRODUCT FEATURES:

Body material: painted sheet metal

Water supply pressure: 2 - 3.5 bar

Operating ambient temperature: 10 - 35 ° C

Supply water temperature (min-max): 10-25 ° C

Supply temperature: 75-80 ° C

Power supply: 220 V- 50 Hz single-phase

On / off switch (present only in the natural version)

Double safety button for hot water

TECHNICAL FEATURES:

Compressor: 1/20 "Hp

Accumulation tank capacity:

- 1,6 l version Plus
- 2,5 l version Natural

Carbonator power: 100 l / h

Carbonator Pump: Volumetric 100 l / h

Recirculation pump: NOT PRESENT

Liters Carbonator: 0,8 l (not present in the Natural version)

Power consumption: 1500 W

Voltage: 230 V- 50 Hz



**CERTIFIED PRODUCT
MATERIALS IN CONTACT WITH WATER**



USABLE UNDER COUNTER DISPENSER



USABLE ONLY WITH DRINKING WATER



**APPLIANCE COMPLIANT WITH A:
D.M. 25/2012 – D.M. 174/2004**

Vertical operation. MAX inlet temperature: 35 ° C.
MAX operating pressure: 3.5bar.

ATTENTION: this equipment requires regular periodic maintenance in order to ensure the potability requirements of the treated drinking water and the maintenance of improvements as declared by the manufacturer. Do not use with microbiologically dangerous water. After periods of inactivity (3-4 weeks) carry out a thorough sanitization or replace the filter.