



H2ONDA Vending

ANN AANN

PRODUCT FEATURES

Body material: Aisi 430 stainless steel and painted sheet metal

Water supply pressure: 2- 3.5 bar

Operating ambient temperature: 10 - 35 ° C

Feed water temperature (min-max): 10-25 ° C

Power supply: 220 V- 50 Hz single-phase

On / off switch (present only in the natural version)

TECHNICAL FEATURES:

Compressor: 1/20" Hp

Accumulation tank capacity:

- 1,6 l version Plus
- 2,5 l version Natural

Carbonator power: 100 l / h

Carbonator Pump: Volumetric 100 l / h

Recirculation pump: NOT PRESENT

Carbonator liters: 0,8 l (not present in the Natural version)

Power consumption: 220 W

Voltage: 230 V- 50 Hz



CERTIFIED PRODUCT
MATERIALS IN CONTACT WITH WATER



USABLE UNDER COUNTER DISPENSER



USABLE ONLY WITH DRINKING WATER



APPLIANCE COMPLIANT WITH A:
D.M. 25/2012 – D.M. 174/2004

Vertical operation. MAX inlet temperature: 35 ° C.
MAX operating pressure: 3.5bar.

ATTENTION: this equipment requires regular periodic maintenance in order to ensure the potability requirements of the treated drinking water and the maintenance of improvements as declared by the manufacturer. Do not use with microbiologically dangerous water. After periods of inactivity (3-4 weeks) carry out a thorough sanitization or replace the filter.